



(12) UK Patent (19) GB (11) 2 107 445 B  
SCIENCE REFERENCE LIBRARY

(54) Title of invention

Rotary regenerative air preheater

(51) INT CL<sup>3</sup>; F28D 17/04

(21) Application No  
8228443

(22) Date of filing  
5 Oct 1982

(30) Priority data

(31) 3140406

(32) 12 Oct 1981

(33) Fed. Rep. of Germany (DE)

(43) Application published  
27 Apr 1983

(45) Patent published  
6 Feb 1985

(73) Proprietor  
Apparatebau Rothemühle  
Brandt & Kritzler GmbH (FR  
Germany),  
Wildenburger Strasse  
5963 Wenden 5  
Rothemühle  
Federal Republic of Germany

(72) Inventors  
Heinz Reidick  
Reinhard Leithner  
Franz-Josef Kirchhoff  
Ernst Puritz  
Siegfried Schluter

(52) Domestic classification  
F4K 24A2 25U



(56) Documents cited  
GB 1572022  
GB 1431289  
GB 1344589  
GB 1330615  
GB 1022356  
GB 0595465  
GB 0311889  
GB 0275231

(58) Field of search  
F4K

(74) Agent and/or  
Address for Service  
Mewburn Ellis & Co.,  
2/3 Cursitor Street  
London EC4A 1BQ

LONDON THE PATENT OFFICE

GB 2 107 445 B



CLAIMS:

1. A rotary regenerative air preheater with capacity for the separate heating of two flows of medium both of which flow to and from the heat exchange matrix through which a heat-emitting medium also flows, the said two  
5 flows being through a hood at each end of the matrix, the hoods and matrix being relatively rotatable about an axis of rotation, the hoods being invariable in their boundaries but being subdivided internally to define distinct respective paths for the said two flows, the  
10 subdivision being adapted to be adjustable to vary the size and/or position of one of the two flows relative to the other, and the hoods.
2. A rotary regenerative air preheater according to Claim 1 wherein there are three flow-compartments within  
15 the hoods, two being respectively occupied by the two flows, the third being connectable to either of the other two.
3. A rotary regenerative air preheater according to Claim 1 wherein walls forming the subdivision are movable  
20 in rotation relative to the radial boundaries of the hoods, about the axis of rotation of the preheater.
4. A rotary regenerative air preheater according to Claim 1 or Claim 3 wherein walls forming the subdivision are or are also radially adjustable.
- 25 5. A rotary regenerative air preheater according to Claim 1 wherein walls forming the subdivision are pivot-

able about an axis lying eccentric of the axis of relative rotation of the preheater whereby to enable division of the hoods either tangentially or radially.

6. Rotary regenerative air preheater substantially as herein described with reference to and as illustrated  
5 in Figs. 1 and 2; Figs. 3 and 4, Figs. 5 and 6, Figs. 7 and 8, Figs. 9 and 10 or Figs. 11 and 12 of the accompanying drawings.

---